

# Using Connector/Carabiner in Mountain Rescue Organizations

20171021-TER-REC0001 Terrestrial Rescue Recommendation

## 1. Introduction

This recommendation was raised after the failure of a central connector made of aluminum during a rescue operation in Zermatt (1998).

Central or main connectors are essential components of any organized rescue system and should provide a good margin of safety in terms of strength and construction that minimizes the ways in which a component may fail.

A number of different standards relate to connectors/carabiners including:

- EN 12275: Mountaineering equipment - connectors - safety requirements and test methods.
- EN 362: Personal Protective Equipment against falls from height - connectors
- NFPA 1983: Standard of Life Safety Rope and Equipment for Emergency Services.

This recommendation includes components used to attach to helicopters except where they are covered by ICAR Air Commission recommendation AIR-REC0014-HEC-HHO-Equipment.

## 2. Recommendation

The ICAR Terrestrial Rescue committee recommends at organized mountain rescue operations for main/central attachment points and for air rescue operations only the use of:

- Triple action gate carabiners or
- Connectors/carabiners with a screw gate.
- Connectors/carabiners must conform to EN 12275 or EN 362 and/or NFPA 1983 US-Standard
- Steel main or central connectors if used with air rescue.

Connectors/carabiners used in flight rescue operations as a part of the equipment of the crew or helicopters are regulated by an extra recommendation AIR-REC0014HEC-HHO-Equipment from the ICAR Air Rescue Commission.

## 3. Explanatory notes

Although this recommendation relates to connector, careful evaluation of equipment and components is required to ensure the best possible levels of safety during organized mountain rescue incidents and training.

In addition, the team using the equipment/components requires training and careful assessment of the equipment's suitability any time it is used.

The adoption of EN standards and/or NFPA 1983 standards is widely accepted across many areas of rescue. These standards offer assurance that the equipment has been manufactured and tested to agreed performance criteria including minimum breaking strains, safe working loads and/or working load limits.

For flight operations, steel is the preferred material for organized mountain rescue activities. Steel has historically a better performance when subjected to the flight environment (steel tends to deform before failure so allows some warning, aluminum has a risk of a sudden fragile fracture type failure with little or no warning).

#### 4. Glossary

NFPA	National Fire Protection Agency - a US agency that provides peer reviewed consensus based standards.
EN	A European Standard that has been ratified one of 3 European Standard Organizations.
Connector	Connectors are a generic term used by EN 362 and EN 12275, carabiners and maillon rapide/quick links are forms of connectors.
Main/central attachment point	At anchor systems, there is a main attachment point for devices used to control the rescue. The location where all the ropes are brought together and the rescuer(s)/stretcher/casualties are also attached can also be considered as a "main or central" attachment point. There is also the "main" attachment point onto a rescuer's harness – which actually may be a tie in rather than a clip in point using a connector.

History of Revisions	
issued	1998 Aosta
revised	2005 Cortina
revised	2017 Soldeu